



333 RT. 17 N.

Mahwah, NJ 07430

800-FOR-HYTORC

CERTIFICATE OF CALIBRATION

TOOL MODEL: J-GUN AIR-8 APACHE DUAL SPEED

J8P00082

PRESSURE / TORQUE CONVERSION CHART

Standard Torque

PRESSURE		TORQUE		
psi	bar	ft-lbs	kgf-m	N-m
20	1.38	2079	287	2818
25	1.72	2581	357	3500
30	2.07	3085	426	4182
35	2.41	3588	496	4864
40	2.76	4091	566	5546
45	3.10	4538	627	6153
50	3.45	4976	688	6746
55	3.79	5414	748	7340
60	4.14	5851	809	7933
65	4.48	6329	875	8581
70	4.83	6834	945	9266
75	5.17	7339	1015	9951
80	5.52	7844	1085	10635
85	5.86	8282	1145	11229

Torque values determined using 10 ft length hose

Calibrations are per ISO5393 Soft Joint Standard.

NOTE: 1) Minimum 30 CFM air required to use this pneumatic torque tool. 2) Use 1/2" or 3/4" diameter hose for optimal results; minimum diameter hose to be used is 1/2".

www.TORCGUN.COM

V5.1 09/16/2014

9/16/2014

LOOK US UP ON FACEBOOK AND TWITTER"